

you can
Canon

imagePRESS C7000VP/C6000VP

High Volume Digital
Colour Production

Make the biggest imPRESSion on your business

For the most complex jobs turn to Canon's flagship Digital Colour Production engines. Delivering exceptional quality and maximum productivity across all media types and weights, the imagePRESS C7000VP and imagePRESS C6000VP satisfy your most demanding production requirements.



COLOUR imagePRESS C7000VP/C6000VP

Incredible quality

Vivid colours and outstanding pin-sharp images that look and feel like offset production.

Precision printing

Precision printing with automatic page-by-page image and density controls provide exceptional consistency for true "production safe" colour.

Exceptional consistency

Maximum Productivity

Full production speeds of up to 70 ipm are achieved across all media types and weights up to 300 g/m² for deadline-beating performance.

A sizeable 10,000 sheets paper supply with up to 8 different sources is

complemented by air-assisted feeding for exceptional reliability and over 2 hours of uninterrupted production.

Exceptional reliability

Highly innovative

Canon's V-toner with its ultra-fine particle size and oil-less fusing characteristics combine with enhanced image control technologies to provide gloss optimisation for an optimal finish on all media.

Exceptional finishing

Choose from a huge diversity of in-line finishing possibilities including perfect binding. Intelligent Registration technology ensures impressive results print after print.

Exceptional image quality and productivity.



imagePRESS

Specifications imagePRESS C7000VP / C6000VP

imagePRESS C7000VP MARKING ENGINE Recommended monthly volume		C7000VP: 70,000 to 300,000 pages (A4) C6000VP: 50,000 to 250,000 pages (A4)	
Maximum monthly volume		C7000VP: 550,000 pages (A4) C6000VP: 515,000 pages (A4)	
Resolution		1,200dpi, 256 gradations	
Registration tolerance		+/- 0.5mm (front to back)	
HDD capacity (Scan and Mailbox)		2 x 80 Gb	
Image memory (SDRAM)		1.5 Gb	
Media weight		64-300 g/m ²	
Paper deck (Marking Unit)		2,000 sheets total (200mm)	
2 Drawers		10,000 sheets max	
Paper feeding capacity		17,000 sheets max	
Paper finishing capacity		2,580 x 992 x 1,040mm (excluding Control Panel)	
Dimensions (W x D x H)		1,200 Kg (including Colour Image Reader)	
Weight		400V, (3-phase), 32A	
Power			
PRODUCTIVITY			
Size	Weight (g/m²)	C7000VP Simplex (ppm) Duplex (ipm)	C6000VP Simplex (ppm) Duplex (ipm)
A4	64 to 300 g/m ²	70.0 65.4	60.0 60.0
A3	64 to 300 g/m ²	36.0 36.0	30.8 30.8
SRA3	64 to 300 g/m ²	33.6 33.6	28.8 28.8
13x19.2"	64 to 300 g/m ²	31.0 31.0	26.6 26.6
COLOUR IMAGE READER-H1 (REQUIRES DADF OR PLATEN COVER)			
Scanning lamp		Xenon tube (Light intensity: 120,000 lx)	
Resolution		600 x 600dpi	
Scanning speed		80ipm (300dpi) 50ipm (600dpi)	
Dimensions (W x D x H)		732 x 595 x 105mm	
Weight		17.5 Kg	
DADF-R1			
Original document size		A4, A3, A5, LGL, LTR, Custom sizes (148 x 210mm to 297 x 420mm)	
Maximum document weight		A4, A5: 216 g/m ² (Single-sided / double-sided) A3: 216 g/m ² (Single-sided), 200 g/m ² (Double-sided)	
Tray capacity		100 sheets (80 g/m ²)	
Document size detection		Length: photo sensor Width: slide guide	
Document process speed (copying)		50ipm (single-sided) - A4, 600dpi 25ipm (double-sided) - A4, 600dpi	
Dimensions (W x D x H)		646 x 570 x 143mm	
Weight		21.5 Kg	
POD DECK-A1 (PRIMARY POD AND SECONDARY POD)			
POD Deck-A1 (Primary)		4,000 sheets (80 g/m ²) (410mm) total	
3 Drawers		4,000 sheets (80 g/m ²) (410mm) total	
POD Deck-A1 (Secondary)		4,000 sheets (80 g/m ²) (410mm) total	
3 Drawers		Air separation method	
Pickup method		Thin (64 to 79 g/m ²) Plain (80 to 105 g/m ²) Thick (106 to 300 g/m ²) Recycled (64 to 256 g/m ²) Coloured (64 to 79 g/m ²) 1-side coated (80 to 300 g/m ²) 2-side coated (80 to 300 g/m ²) Embossed paper, (80 to 300 g/m ²) Vellum paper (64 to 300 g/m ²) Bond paper, Punched paper (64 to 105 g/m ²) Tab paper (151 to 209 g/m ²) (A4) Transparency (A4, A4R) Label (A4, A3, B4) Postcard	

Paper sizes (POD Decks & Standard Paper Trays)		A4, A4R, A3, SRA3, B4, JIS-B5, JIS-B5R, LGL, LTR 13" x 19.2" (330.2 x 487.7mm) 12" x 18" (305 x 457mm) 11" x 17" (279 x 432mm) 4-pane postcard Custom sizes (182 x 182mm to 330 x 487mm)	
Paper level detection		Visual display	
Double feeding detection		Yes (primary POD deck)	
Escape tray		Yes (primary POD deck)	
Dimensions (W x D x H)		Primary POD: 977 x 1040 x 792mm Secondary POD: 811 x 1040 x 792mm	
Weight		246 Kg	
Power		240V, 10A	
HIGH CAPACITY STACKER-C1			
Paper type		Stacker Dolly (64 to 300 g/m ²)	
Output tray (64 to 300g/m ²)		A4, A3, SRA3, B4, 11"x17", 12"x18", 13"x19.2" Tab Paper (A4, LTR), Custom size (216 x 182mm to 330 x 487mm)	
Downstream output (64 to 300g/m ²)		A4, A4R, A3, SRA3, B4, 11"x17", 12"x18", 13"x19.2" Tab Paper (A4, LTR), Custom size (182 x 182mm to 330 x 487mm)	
Tray capacity		Stack tray: 5,000 sheets (80 g/m ²) (570mm) Output tray: 1,000 sheets (80 g/m ²) (100mm)	
Dimensions (W x D x H)		860 x 765 x 1,290mm	
Weight		200 Kg	
Power		240V, 300W	
One stacker unit		240V, 600W	
PERFECT BINDER			
Bookbinding Method		Hot Glue Spine with Wraparound Cover	
Bookbinding Thickness		Approx. 10 to 200 sheets (1mm to 25mm)	
Book Size		SRA4 (Maximum Before Trimming)	
Margin Trimming		Integral trimming device - 3 Sides, 1 side or no trimming	
Insertion Unit Capacity		Upper Tray: 200 sheets (A4 80 g/m ²) Lower Tray: 200 sheets (13"x19.2" 80 g/m ²)	
Cover Size		Up to 13" x 19.2"	
Paper Weights		64 - 163 g/m ² (Insertion sheets) 64 - 300 g/m ² (Cover sheets)	
Power Source		240V, 10A	
Dimensions (H x W x D)		1360mm x 920mm x 783mm	
Weight		Approximately 324 Kg	
FINISHER-AB1			
Paper Weight		64 to 300 g/m ²	
Paper Size		As supported by Marking Engine	
Paper size (staple)		A4, A4R, A3, B4, JIS-B5	
Stacking capacity (Non-stapled)		Tray A: 3,000 sheets Tray B: 2,000 sheets	
Stacking capacity (Stapled)		Tray A: 100 sets Tray B: 100 sets	
Staple capacity		A4, A4R, B4, B5 A3	
Staple cut		100 sheets (80 g/m ²) max 50 sheets (80 g/m ²) max	
Dimensions (W x D x H)		800 x 792 x 1,180mm	
Weight		126 Kg	
Power		240V, 250W max	

SADDLE FINISHER - AB2		Paper type (booklet making)	
Paper size (booklet making)		64 to 200 g/m ² (inner pages), up to 300 g/m ² (cover) A3, A4R, B4, SRA3, 12"x18", 11" x 17", LGL, LTR	
Stacking capacity		30 booklets (80 g/m ²)	
Booklet sheets		2 to 20-sheets (80 g/m ²)	
Dimensions (WxDxH)		800 x 792 x 1,180mm	
Weight		178kg	
Power		240V, 8A	
BOOKLET TRIMMER-C1			
Type		Leading-edge trimmer with delivery tray	
Maximum number of sheets trimmable		40 sheets (80 g/m ²), 38 sheets (80 g/m ²) + 2 sheets (300 g/m ²) All sizes supported by Saddle Finisher-AB2	
Possible trimming size		30 booklets	
Conveyor Capacity		1,575 x 792 x 1,040mm	
Dimensions (W x D x H)		Weight: 152 Kg	
Weight		Power: 240V, 4A max	
DOCUMENT INSERTION UNIT - C1			
Original type		Plain paper Coloured paper Coated paper	
Original size		Tray 1: small-size	
Tray 1: small-size		A4, A4R, LTR Custom sizes (182 x 182mm to 330 x 330mm)	
Tray 2: small/large-size		A4, A4R, A3, SRA3, B4, LGL, LTR 13" x 19.2", 12" x 18", 11" x 17" Custom size (182 x 182mm to 330 x 487mm)	
Stacking capacity		200 sheets (80 g/m ²)	
Dimensions (W x D x H)		621 x 679 x 213mm	
Weight		17 Kg	
PUNCHER UNIT - U1/W1/X1			
Paper size		2-hole (U1) 4-hole (W1 or X1)	
Paper weight		A4, A4R, A3, B4 A4, A3 64 g/m ² to 200 g/m ² (not transparency)	
Punch hole diameter		6.5mm	
EYE-ONE PROCESS CONTROL - PRODUCTION			
Colour libraries included		PANTONE® color bridge EC PANTONE® solid coated PANTONE® solid matte PANTONE® uncoated	
Printer verification		Fogra27 Fogra39	
Canon verification		Canon verification	
Package contents		Eye-One Pro Spectrophotometer iO Table Measurement accessories Carrying Case Eye-One Process Control CD	

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change. ® and ©. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

you can
Canon

falcon
We make it simple

FREEPHONE: 0800 08 22224

Head Office: Falcon House, The Forum, Icknield Way, Tring, Herts. HP23 4JX

www.falconcopiers.co.uk



Canon's GENUINE logo means quality all-round performance

